



**NEW!**

**ZP28-6A/9A Pneumatic Automatic Full Range Tension Plastic Strapping Tool**  
**Powerful tension, Max. 350Kgs (3500N) for heavy duty plastic strapping jobs.**



**NEW FEATURES:**

- Enhanced motor structure advanced both tension and sealing performances.
- Enhanced structure of worm and worm wheel to accelerate tension speed.
- More precise and easier adjustment on Tension Force Adjustment Valve.
- Faster and shorter Sealing Time from 0 up to 4.0 seconds.
- New feeder wheel, strapping grippers and tension arm assure stable tension force.
- Lighter product weight.

**SPECIFICATION:**

Model	Air Pressure	Fits Poly Strap	Strap Width		Strap Thickness		Approx. Tension Range	Sealing Efficiency
			mm	inch	mm	inch		
ZP28-6A	6~7 kg/cm <sup>2</sup>	PP	16	5/8	0.75-1.27	.029-.05	20-180kg	85+-5%
	87~101.5psi	PET	13-16	4/8-5/8	0.55-1.27	.022-.05	60-350kg	
ZP28-9A	6~7 kg/cm <sup>2</sup>	PP	16&19	5/8&3/4	0.75-1.27	.029-.05	20-180kg	
	87~101.5psi	PET			0.65-1.27	.026-.05	60-350kg	

**COMPARISON TABLE ZP28-9X V.S. ZP28-9A**

Model	ZP28-9X	ZP28-9A
Worm & Worm Wheel	Standard	New *
Tension Speed	6.3 cm/sec	10.2 cm/sec
Sealing Time Range	0-6 Sec	0-4.0 Sec
Feeder Wheel	Standard	New *
Strapping Gripper	Standard	New *
Tension Arm	Standard	New *
Tool Weight	4.2 Kgs	4.1 Kgs